



- 1 Design pressure 300PSI(2.1MPa)
- 2 Design temperature 150°F(66°C)
- 3 Min. allowable temperature 14°F(-10°C)
- 4 Working medium, water PH 3-11
- 5 Internal permeate pressure not to exceed 125PSI(0.88MPa)
- 6 Please operate according to directions
- 7 Subject to chance without notice, please sign in the website of the company to inquire.(www.ropv.com.cn)

12	GB/T70.1 M6x20	Locking Crescent Screw	4	304SS	
11	4013.1	Plug	1	Engineering Thermoplastic	
10	4010	Saddle	2~3	Rubber	
09	GB/T5782 M8x60	Strap Screw	4~6	304SS	
08	4008	Strap	2~3	304SS	
07	12.5x1.8G GB/T3452.1 19x2.65G GB/T3452.1	O-Ring	4	EPDM	
06	14x2.65G GB/T3452.1 17x2.65G GB/T3452.1	O-Ring	2	EPDM	
05	4011	Locking Crescent	4	304SS	
04	4021.1 4021	Adapter Adapter	2	ABS	for flat membrane
03	90x5.3G GB/T3452.1	O-Ring	2	EPDM	
02	4033.1 4033Z	End Plate	2	Engineering Thermoplastic	for flat membrane
01	4028.1-6	Pressure Shell	1	FRP	Opt for blue or white
Ref	Part Number	Description	Qty	Material	Note

Shell Length Code	Shell Number	L L.O.A (MM/IN)	S Span (MM/IN)	Approx assembly weight (KG/LB)
1	4028.1	1263/49.7	600/23.6	7/15.8
2	4028.2	2279/89.7	1200/47.2	11/24.8
3	4028.3	3295/129.7	2200/86.6	14/31.5
4	4028.4	4311/169.7	1600/63.0x2	18/40.5
5	4028.5	5327/209.7	2300/90.6x2	21/47.3
6	4028.6	6343/249.7	2700/106.3x2	25/56.3

  

<b>ROPV</b>	DESIGN	<b>Harbin ROPV Industry Development Center</b>	
	REVIEW	MODEL	R4040B300E PRESSURE VESSEL
	APPROVAL	DRG	R4040B300E-00
		REV	10